



UV STERILISER

It is equipped with low pressure UV-lamps, powered by electronic high frequency ballasts, for highest efficiency and lowest power consumption.

The sterilization process is microprocessor-controlled via data from the UV-sensor. The intelligent lamp monitoring system will, in case of any lamp failure, inform the user of this occurrence as well as the location of the broken lamp.

The hour meter tells the user to change lamps when the limit of its using time is reached.

All necessary data is available in a display window on the control cabinet.

Sweden
JOWA AB
 Tulebovägen 104
 S-428 34 Källered
 Telephone: +46-31 726 54 00
 Telefax: +46-31 795 45 40
 website: www.jowa.se
 e-mail: info@jowa.se

Norway
JOWA NORGE A/S
 Solbergveien 22
 3057 Solbergelva
 Telephone: +47-3223 6700
 Fax: +47-3223 6701
 e-mail: post@jowa.no

Germany
JOWA GERMANY GMBH
 Hansestrasse 21 / Haus 2
 18182 Rostock-Bentwisch
 Telephone : +49-381 6302 660
 Fax : +49-381 6302 641
 website: www.jowa.de
 e-mail: info@jowa.de

Netherlands
JOWA HOLLAND
 Ebweg 61
 2991 LS Barendrecht
 Telephone : +31(0)180 55 71 33
 Fax : +31(0) 180 61 11 27
 e-mail: post@jowa-holland.nl

USA
JOWA CONSILIUM US, INC.
 59 Porter Road
 Littleton, MA 01460
 Telephone: +1-978 486 98 00
 Fax: +1-978 486 01 70
 website: www.jowa-consilium.com
 e-mail: info@jowa-consilium.com

Singapore
JOWA (S) PTE., LTD.
 26, Lorong G Telok Kurau
 Singapore 426195
 Telephone: +65-6872 8802
 Fax: +65-6872 8896
 e-mail: jowaspdk@singnet.com.sg

China
JOWA (Shanghai)
Marine Equipment Co.,Ltd.
 5111 Luo Shan Road, Pudong New Area
 Shanghai 201204
 Telephone: +86-21-3390 6890
 Fax: +86-21-3390 7550
 e-mail: jowasha@jowa.com.cn

For many decades now, Jowa has been a trusted and reliable supplier of technical environmental protection equipment to the shipping industry. We can offer every conceivable service for installation, supervision, operation, monitoring and control of Jowa's equipment. You can choose between our own personnel or one of our trained representatives all over the world.

THE JOWA GROUP



Flow capacity

Maximum flow at different water qualities (m³/h). Normally the Max/Min capacity of a UV-unit is chosen between T50=90% down to T50=60%.

	T10=100%	T10=98%	T10=96%	T10=93%	T10=90%	T10=87%	T10=83%
Size	T50=100%	T50=80%	T50=80%	T50=70%	T50=60%	T50=50%	T50=40%
UV1	1.41	1.28	1.15	1.01	0.88	0.74	0.60
UV2	1.98	1.79	1.61	1.42	1.24	1.04	0.85
UV3	4.59	4.05	3.51	3.01	2.53	2.06	1.62
UV4	6.98	6.13	5.30	4.54	3.82	3.13	2.49
UV5	12.49	10.52	8.73	7.17	5.79	4.55	3.45
UV31	15.88	14.00	12.14	10.41	8.75	7.13	5.60
UV41	24.09	21.13	18.28	15.67	13.21	10.86	8.66
UV51	43.20	36.39	30.19	24.82	20.03	15.73	11.94

Maximum flow at different water qualities, [m³/h]

Normally the Max/Min capacity of a UV-unit is chosen between T50=90% down to T50=60%

Technical data

Voltage:	110/230 VAC 50/60 Hz
Power consumption:	35-290W depending on size
UV-dosage:	36000 Ws/cm ²
Alarm:	Open/closed 1A resistive Relay output, normally
Working pressure:	Max 10 bar
Material chamber:	Stainless Steel 316L
Weight:	15-25 kg (up to sizes)

Main Features

- » Individual lamp monitoring system
- » LCD display
- » UV-sensor standard
- » Low power consumption
- » Compact design in stainless steel 316L
- » Always with solenoid valve